

## Specially designed for environmental engineering

- Large readable display
- Accurate and easy-to-use
- Robust ABS casing
- Time-stamped monitoring
- Differential measurements
- Auto-Stop

### Typical applications:

- ✓ Choking of the filters (differential pressure) on air conditioning installations
- ✓ Pressure loss in ventilation ducts
- ✓ Tightness control for gas ducts
- ✓ Pressure for natural gas transportation and distribution (20 mbars), propane/butane (37 or 50 mbars)

Measurement range	0 to 138 mbar
Maximum pressure	1.38 bar
Resolution	0.1 mbar
Accuracy	0.3 % full scale
Response time	0.5 s
Unit selection	psi, bar, mbar, inH <sub>2</sub> O, mmH <sub>2</sub> O

### Operating conditions:

- Temperature: 0 to 50 °C
- Humidity: < 80 % RH

### Storing conditions:

- Temperature: -20 °C to +60 °C
- Humidity: < 80 % RH

**Power supply:** 1 x 9 V battery

**Dimensions:** 72 x 182 x 30 mm

**Mass:** 220 g (battery included)



Supplied in hard case  
with accessories

# C.A 852

## Digital Manometer

## Pressure

Food Service  
Industry



HVAC systems



Production



Industrial  
Refrigeration



Electrical,  
Mechanical  
Maintenance

Storage

To order

**C.A 852 Manometer**

P01.1841.02

[www.test-meter.co.uk](http://www.test-meter.co.uk)

is a trading name of

PAT Training Services Ltd

Glendale's House, 607 York Road, Leeds, LS9 6NW

Tel: 0113 248 9966 Fax: 0113 248 4276

[admin@test-meter.co.uk](mailto:admin@test-meter.co.uk)