



Specification  
MM94 TRMS Digital Multimeter



**ELECTRICAL**

All specified accuracies are at 23°C ± 5°C, <70% R.H. for 1 year.

**Temperature coefficient:**

0.1 x (specified accuracy) per °C. (0°C to 18°C, 28°C to 50°C).

All accuracies below are expressed as ± (percentage of reading + digits)

**DC Voltage**

Range	Resolution	Input impedance	Accuracy
600mV	0.01mV	10MΩ	0.08% + 5
6V	0.0001V	11MΩ	
60V	0.001V	10MΩ	
600V	0.01V		
1000V	0.1V		

Overload protection: 1000V DC or 750V AC rms



Specification  
MM94 TRMS Digital Multimeter

**AC Voltage (True RMS)**

Range	Resolution	Input impedance	Accuracy			
			HFR1 selected 45 to 60Hz	HFR2 selected		
				45Hz to 500Hz	500Hz to 1kHz	1kHz to 2kHz
600mV	0.01mV	10MΩ	2.0% + 20	1.0% + 20	1.5% + 20	N/A
6V	0.0001V	11MΩ				
60V	0.001V	10MΩ		2.0% + 20	1.5% + 20	2.0% + 20
600V	0.01V					
750V	0.1V					

AC coupled true rms AC voltage accuracy is specified from 2% to 100% of range.

Crest factor: 3 at full scale, 6 at half scale

High frequency reject filter -3dB points: HFR1 at 1kHz, HFR2 at 100kHz

Peak hold accuracy (45Hz to 500Hz): 60V to 750V AC ± (3.0% rdg + 500 dgts)

Peak hold response time: 1ms

Overload protection: 1000V DC or 750V AC rms

**AC + DC Voltage (True RMS)**

Range	Resolution	Input impedance	Accuracy		
			45Hz to 500Hz	500 Hz to 1 kHz	1 kHz to 2 kHz
600mV	0.01mV	10MΩ	1.5% + 30	2.0% + 30	N/A
6V	0.0001V	11MΩ			
60V	0.001V	10MΩ			1.5% + 30
600V	0.01V				
750V	0.1V			2.5% + 30	



Specification  
MM94 TRMS Digital Multimeter

AC coupled true rms AC voltage accuracy is specified from 2% to 100% of range.

Crest factor: 3 at full scale, 6 at half scale

Overload protection: 1000V DC or 750V AC rms

**Current**

Range	Resolution	Voltage burden	Accuracy		
			DC	AC (true rms) 45 Hz to 1 kHz	AC+DC (true rms)
600μA	0.01μA	500mV	0.5% + 10	1.5% + 20	2.0% + 30
6000μA	0.1μA	2V			
60mA	0.001mA	500mV			
400mA	0.1mA	2V	1.0% + 10	2.5% + 20	3.0% + 30
20A Note 1	1mA		2.0% + 10		

AC coupled true rms AC current accuracy is specified from 2% to 100% of range.

Crest factor: 3 at full scale, 6 at half scale

Peak hold accuracy on AC current ranges (45Hz to 500 Hz):

± (3.5% rdg + 500 dts)

Peak hold response time: 1ms

Input protection: 0.5 A/1000 V fast blow ceramic fuse on 600μA to 400mA ranges  
20A/600V fast blow ceramic fuse on 20 A range

Note 1: Apply currents >10 A for 30 seconds maximum, then allow a 10 minute cooling period.



Specification  
MM94 TRMS Digital Multimeter

**Resistance**

Range	Resolution	Open circuit voltage	Accuracy
600Ω	0.01Ω	-3.0V dc	0.3% + 20
6kΩ	0.0001kΩ		
60kΩ	0.001kΩ		
600kΩ	0.01kΩ		
6MΩ	0.0001MΩ		
60MΩ	0.001MΩ		1.0% + 10
			3.0% + 20

Overload protection: 600V DC or AC rms

**Conductance (6000 counts only)**

Range	Resolution	Open circuit voltage	Accuracy
60nS	0.01nS	-0.7V dc	1.0% + 10

Overload protection: 600V DC or AC rms

**Capacitance (6000 counts only)**

Range	Resolution	Accuracy
6nF	0.001nF	3.0% + 30
60nF	0.01nF	3.0% + 10
600nF	0.1nF	
6μF	0.001μF	
60μF	0.01μF	
600μF	0.1μF	
6mF	0.001mF	5.0% + 10

Overload Protection: 600V DC or AC rms



Specification  
MM94 TRMS Digital Multimeter

**Frequency**

Range	Resolution	Trigger level	Accuracy
60Hz	0.001Hz	>1.5V	0.1% + 10
600Hz	0.01Hz		
6kHz	0.0001kHz		
60kHz	0.001kHz		
600kHz	0.01kHz		
6MHz	0.0001MHz	>2.5V, <5V	0.1% + 10
10MHz	0.001MHz		

Minimum input: >6Hz  
 Minimum pulse width: >100 ns  
 Duty cycle limits: >30% and <70%  
 Overload protection: 600V DC or AC rms.

**Duty Cycle**

Range	Resolution	Resolution	Pulse width	Accuracy (5V logic)
5% to 95%	40Hz to 1kHz	0.1%	>10µs	2.0% + 10
10% to 90%	1kHz to 10kHz			
20% to 80%	10kHz to 20kHz			

Overload protection: 600V DC or AC rms



Specification  
MM94 TRMS Digital Multimeter

**Temperature** (Type K Thermocouple)

Range	Resolution	Accuracy
0°C to 400°C	0.1°C	1.0% + 1°C
-50°C to 0°C, 400°C to 1300°C		2.0% + 3°C
32°F to 750°F	0.1°F	1.0% + 2°F
-58°F to 32°F, 750°F to 2372°F		2.0% + 6°F

Overload protection: 30V DC or AC rms

**Continuity**

Range	Resolution	Response time	Open circuit voltage	Audible indication
600Ω	0.01Ω	100 ms approx.	-3.0V dc	<40Ω

Overload protection: 600V DC or AC rms

**Diode Test**


Range	Resolution	Test current	Open circuit voltage	Audible indication	Accuracy
2V	0.1 mV	0.5 mA typical	3.0V dc typical	<0.05V dc	2.0% + 10

Overload protection: 600 V DC or AC rms



Specification  
MM94 TRMS Digital Multimeter

**GENERAL**

Display: Liquid crystal display  
 Digital, 60000 counts, updates 2/sec  
 Polarity: Automatic, positive implied, '-' for negative polarity indication  
 Overrange: (OL) or (-OL) is displayed  
 Bar-graph, 60 segments, updates 20/sec  
 Power: 9V, PP3 alkaline batteries (IEC 6LR61, NEDA 1604A)  
 Battery life: 50 hours typical with alkaline  
 Low battery indication: The LCD will display   
 Auto power off: After 30 minutes  
 Fuses: 0.5 A/1000V 6.3x32mm fast blow ceramic fuse  
 20 A/600V 10x38mm fast blow ceramic fuse  
 Dimensions: 198 x 90 x 44mm  
 Weight: Approx. 400g, including battery  
 Includes: TL16 test leads, TT1P Type K thermocouple, 9V PP3 battery (installed), instructions

**ENVIRONMENTAL**

Temperature & Humidity (Operating): 0°C to 50°C <70% R.H.  
 (Storage): -20°C to 60°C <80% R.H.  
 Altitude: up to 2000m  
 Pollution degree: 2, indoor use

**SAFETY**

Conforms to BS EN 61010-1, BS EN 61010-2-033, CAT IV 600V, CAT III 1000V  
 Class II, double insulation

**EMC**

Conforms to BS EN 61326-1



Specification  
MM94 TRMS Digital Multimeter

**SPECIFICATION FOR TL16 TEST LEADS**

Maximum voltage: 1000V AC/DC  
 Maximum current: 10A continuous  
 Connector: 4mm banana plug with fixed shroud  
 Environmental  
 Temperature (Operating & Storage): 0°C to 40°C  
 Altitude: up to 2000m  
 Pollution degree: 2

**Safety**

Conforms to BS EN 61010-031,  
 CAT IV 600V, CAT III 1000V, 10A (Probe tip caps fitted)  
 CAT II 1000V, 10A (Probe tip caps removed)  
 Class II, double insulation



Martindale Electric Company Limited  
 Metrohm House, Imperial Park, Imperial Way,  
 Watford, Hertfordshire, WD24 4PP, UK  
 Tel: +44 (0)1923 441717 Fax: +44 (0)1923 446900  
 E-mail:sales@martindale-electric.co.uk  
 Website: www.martindale-electric.co.uk



© 2016 Martindale Electric Company Ltd.  
 Registered in England No. 3387451. Rev1 LITMM94