

Available at



Megger.

MFT1711, MFT1721 and MFT1731
Multifunction Tester

MFT1711, MFT1721 and MFT1731 Multifunction Tester



- Simple colour-coded test selection with large clear backlit display for ease of use
- Two and three wire non-trip loop testing for RCD protected circuits
- Type-B RCD and 3-phase RCD testing for industrial applications with no Earth
- 3-terminal earth test and stakeless testing for electrode resistance measurement
- Internal memory and Bluetooth® communications
- EN61010 CAT IV safety rating and tough IP54 case

DESCRIPTION

The MFT1700 series is a range of 3 instruments for testing low voltage electrical installations to BS7671. They provide all the tests required to complete the necessary electrical certification for industrial, commercial and domestic fixed wiring installations, including:

- ⌘ System voltage and frequency measurement TRMS
- ⌘ Insulation test at 100 V*, 250 V, 500 V and 1000 V Including input protection against live circuits up to 600 V even when insulation test is locked-on
- ⌘ Continuity resistance at 200 mA or 15 mA
- ⌘ Automatic start - no need to press TEST so leaving both hands free to hold probes
- ⌘ Resistance range up to 100 kΩ with fast continuity buzzer at selectable thresholds
- ⌘ Earth loop test
- ⌘ 2 and 3 wire non-trip range
- ⌘ 2 wire Hi current including phase to phase
- ⌘ Prospective fault current measurement up to 20 kA
- ⌘ RCD testing including:
 - Type AC, A, S, B* and programmable RCDs
 - 3-phase RCDs*
 - Auto-test routine
 - Fault (Touch) voltage display
- ⌘ Earth spike testing
 - 2-pole/3-pole
 - ART
 - Stakeless techniques

low voltage systems with no protective device, so safe for connection anywhere on the system right up to the source transformer without risk of damage from large transient spikes.

The unique modern styling allows it to be operated while stood on the floor, a ladder-shelf or platform, hung around the neck or handheld. Dual TEST and LOCK buttons - one pair at each end - makes the testers easy to operate left or right handed.

Quick to pick up and use, the controls are colour coded to make range selection easy and fast. They also reduce the chance of using the wrong function or range. The large crystal clear backlit display uses the patented Megger digital/analogue arc, providing indication of fluctuating readings while the dual digital readout shows precise values of key measurements simultaneously with the test parameters, such as the output voltage on insulation testing as well as the resistance value in MΩ.

Visible and audible safety warnings are paramount when testing high-energy systems and the MFT1700 series includes full input protection and safety warnings when a hazardous voltage is present. If live voltages exist on a circuit during insulation or continuity testing, the voltage is displayed on the screen. If this voltage exceeds a safe level, further testing is inhibited and a warning beep sounds.

The MFT1731 features internally rechargeable batteries and charger with a charge time of less than 4 hrs, so reducing the cost of ownership.

Fully compliant with all requirements of IEC 60364 derived standards

All instruments are IEC 61010 CAT IV 300 V rated for connection to



Megger.

including VDE 0100 and BS 7671, the new MFT includes all the latest measurement technology in a light-weight compact design, fully protected and usable on single phase and 3 phase installations.

Key measurement functions include two and three wire non-trip loop test technology for fast repeatable results, comprehensive testing of RCDs including type B, and integrated 3-terminal and stakeless clamp techniques for earth electrode testing.

The MFT1731 includes built-in memory and Bluetooth communications for downloading test results using Megger Download Manager (supplied). As an option, the MFT1731 is available complete with PowerSuite® Lite software as the MFT1731 On-Site. PowerSuite provides a professional solution to certification with electronic form completion from stored data within the MFT, either downloaded to a mobile device such as a Smartphone, or direct to a PC. See the separate datasheet on Megger PowerSuite software for further details.

The new MFT1700 series has been designed for tough environments

MFT1711, MFT1721 and MFT1731 Multifunction Tester

and ultimate reliability. Features include a rubber over mould for extra protection and grip, IP54 protection against dust and water and an EN61010 Cat IV safety rating. Its class leading input protection ensures the MFT can withstand accidental misuse and voltage transients when other testers can't.

All this in an intuitive and easy to use instrument with no hidden menus or complicated screens. Tests are easily selected using the colour coded rotary switches with results clearly displayed on the high contrast, dual measurement, backlit display.

Included with the instrument: standard 3-wire leadset and a mains test lead, a switched probe for fast and easy testing*, a full 12-month calibration certificate and warranty upgradeable to 3 years. The MFT1711 and MFT1721 are supplied in a robust moulded case, and the MFT1731 is supplied in a large soft pouch with plenty of additional space for optional extras like a few tools and the earth electrode test kit, comprising 2 spikes and 3 long test leads.

PRODUCT SELECTION CHART

	MFT1711	MFT1721	MFT1731
Insulation ranges			
100 V		■	■
250 V, 500 V	■	■	■
1000 V	■	■	■
Test voltage display	■	■	■
Adjustable buzzer threshold		■	■
Continuity and resistance ranges			
200 mA test	■	■	■
15 mA test		■	■
Adjustable buzzer threshold	■	■	■
Loop testing			
2 and 3 wire non-tripping L-PE 50 V ~ 280 V	■	■	■
2 wire Hi current L-N 50 V ~ 280 V	■	■	■
2 wire phase to phase L-L 50 V ~ 500 V		■	■
PSCC and PFC (20 kA max.)	■	■	■
Max. Zs display	■	■	■
R1 + R2 value		■	
Touch voltage display on faulty earth	■	■	■
Earth electrode test			
2 and 3 pole **			■
3 pole ART and Stakeless method **			■

* model dependant

** requires optional accessory

	MFT1711	MFT1721	MFT1731
RCD tests			
1/2, 1, 5 x I and ramp RCD test	■	■	■
Auto RCD test	■	■	■
Type AC, A and S RCDs	■	■	■
Type B (pure DC) RCDs		■	■
Programmable RCD	■	■	■
3-phase RCD (no earth)		■	■
30, 100, 300 and 500 mA RCD	■	■	■
10 mA and 1000 mA RCD	10 mA	■	■
Other features			
Supply measurement	■	■	■
True RMS	■	■	■
Leakage current measurement **		■	■
Phase rotation		■	■
Calibration certificate	■	■	■
Rechargeable batteries (charger included)			■
SP5 Switched probe included		■	■
Warranty upgradeable to 3 years FREE	■	■	■
On board memory with Bluetooth download			■
CAT IV 300 V / CAT III 600 V	■	■	■
Hard moulded case	■	■	
Soft pouch with additional storage			■

**Megger****MFT1711, MFT1721 and MFT1731**
Multifunction Tester**SPECIFICATIONS****Insulation test**

Output voltage	-0% +20% at rated load or less
Voltage display	±3% ±3 digits ±0.5% of rated voltage
Short circuit current	1.5 mA nominal test current
Test current on load	1 mA at min pass values of insulation

Insulation accuracy

1000 Volts	10 kΩ ~ 999 MΩ	±3% ±2 digits
500 Volts	10 kΩ ~ 500 MΩ	±3% ±2 digits
	>500 MΩ	±10% ±4 digits
250 Volts	10 kΩ ~ 250 MΩ	±3% ±2 digits
	>250 MΩ	±10% ±4 digits
100 Volts	10 kΩ ~ 100 MΩ	±3% ±2 digits
	>100 MΩ	±10% ±4 digits

Resistance and continuity

0.01 Ω ~ 99.9 Ω	±2% ±2 digits
100 Ω ~ 99.9 kΩ	±5% ±2 digits

Open circuit voltage

5 V ±1 V

Test current

(0 Ω ~ 2 Ω)
205 mA ±5 mA
15 mA ±5 mA
(user selectable)

Loop test

Live to earth/neutral supply	48 V ~ 280 V (45 Hz ~ 65 Hz)
Live to live supply (not MFT1711)	48 V ~ 500 V†† (45 Hz ~ 65 Hz)
L-N/L-L tests	±5% ±5 digits

L-E tests †

0.1 Ω ~ 39.9 Ω	±5% ±5 digits ± noise margin
40.0 Ω ~ 1000 Ω	±10% ±5 digits

Display range

0.01 Ω ~ 1000 Ω

Live to earth PFC range

20 kA

Live to live PSCC range

20 kA

† Reference conditions apply

†† MFT1711 280 V

For test environments see service data

RCD tests

Supply up to 100 mA	48 V ~ 480 V** (45 Hz ~ 65 Hz)
Supply up to 1 A	48 V ~ 280 V
RCD type	Type AC, A, S
	Type B (pure dc)

No trip test

(1/2xl) -10% ~ -0%

Trip test

(1xl, 2xl & 5xl) +0% ~ +10%

Ramp test**Touch voltage**

(0 ~ 253 V) +5% +15% ±0.5 V

Trip time

±1% ±1 ms

Trip current

±5%

Step increments**VAR (variable RCD selection)**

10 mA ~ 50 mA	1 mA steps
50 mA ~ 500 mA	5 mA steps
500 mA ~ 1000 mA	10 mA steps

Supply measurement

Voltage	10 V ~ 600 V
	(15 ~ 400 Hz) True RMS
	±3% ±1 V ±2 digits

Phase rotation indication

L1-L2-L3 & L1-L3-L2

Frequency

15 Hz ~ 99 Hz ±0.5% ±1 digit

100 Hz ~ 400 Hz ±2.0% ±2 digits

Frequency resolution

0.1 Hz

Power supply

MFT1711 and MFT1721:	IEC LR6 type AA alkaline (6 cells - supplied)
MFT1731:	1.2 V NiMH (rechargeable pack of 6 - supplied)

Mains charger for on-board re-charging (4 hours typical) 12 V car charger
(cigar lighter lead - optional)

Earth / ground test

Resolution	0.01 Ω
Current	0.45 mA or 4.5 mA
Noise rejection	20 V pk/pk (7 V rms)
Max probe resistances	Rp & Rc
	100 kΩ @ 50 V
	5 kΩ @ 25 V
2 & 3 pole method	(0.01 Ω ~ 1.999 kΩ)
	±2.0% ±3 digits
	ART method (1.00 Ω ~ 1.999 kΩ)
	±5.0% ±3 digits**

Stakeless method (1.00 Ω ~ 199 Ω)

±7.0% ±3 digits**

Available at



test-meter.co.uk

13 Heading
H4 HEADING

Current

(via optional clamp meter)

±5.0% ±3 digits.

Range 0.1 mA to 200 A ac

Resolution 0.1 mA

MV sensor input

(MFT1721 and MFT1731)

Including temperature (third party module)

±1.0% ±2 digits

Range 0.0 mV to ±199.9 mV dc

Resolution 0.1 mV

Data storage

(MFT1731)

Capacity: 1000 results

Bluetooth communication

Safety

EC 61010-1:2010

IEC 61010-30:2010

IEC 61010-031:2008

600 V Cat III / 300 V Cat IV (Max Phase to Phase 600 V)

IEC 61557:2007 parts 1 to 10

EMC IEC61326 edition 2 location class B

Operating temperature range and humidity -10 °C ~ +55 °C
90% R.H. at +40 °C max

Storage temperature range and humidity -25 °C ~ +70 °C

Maximum altitude 2000 m

Weight (instrument and case) 1 kg (with batteries, excluding case)

Dimensions (instrument and case) MFT1711 and MFT1721
150 mm H x 85 mm W x 235 mm D

MFT1731
220 mm H x 390 mm W x 285 mm D

IP rating IP54

Calibration temperature +20 °C

Temperature co-efficient <0,1% per °C

For test environments see service data.

The word PowerSuite is a registered trademark of Megger Limited.

The Bluetooth word mark and logo are owned by the Bluetooth SIG, Inc. and any use of such marks by Megger is under licence.

ORDERING INFORMATION

Description	Order Code
MFT1711-BS	1008-121
MFT1721-BS	1008-123
MFT1731-BS	1008-128
MFT1731-PS	1008-130

Included accessories

Printed quick start guide

Full user guide on CD

Calibration certificate

Switched probe SP5 (not supplied with MFT1711) 1002-774

Neck strap - Megger embroidered 2001-509

3 Wire lead set with prods and clips 1001-991

Mains plug test lead (BS1363) (LT300-EN-BS) 6220-810

AC battery charger (MFT1731 only) 1002-736

Optional accessories

PowerSuite Lite 1000-631

Euro mains test lead SIA45 (not AU) 2000-674

Fused 10 A test lead set (red/blue/green) with prods and clips 1001-975

ETL30 Extension Test Lead 30 m 1000-215

ETL50 Extension Test Lead 50 m 1000-217

Cigar lighter adapter for battery charging. 6280-332

Switched Probe SP5 (silicone) 1001-687

ICLAMP Current measuring clamp 1001-012

VCLAMP Voltage inducing clamp, calibration check pcb (for stakeless test) and lead 1001-013

Electrode kit (MFT1731 only) 1001-810

Test and carry pouch 1006-408

Large soft pouch with extra storage 1007-463

SALES OFFICE

Megger Limited
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
E UKsales@megger.com

MFT1711--MFT1721--MFT1731_DS_en_V01

www.megger.com
ISO 9001

The word 'Megger' is a registered trademark

Megger