sola **Product Technical Specifications**



U Cabezal Universal



Mod. BME Maneuvering Poles

Functionality

The maneuvering poles have the function of safeguarding distances of electrical work. These poles have a fixed length. With them the operator can make the detection and earthing (voltage detector and earthing equipment is required) at a safe distance.

Product Features

Maneuvering pole, composed of only section made of polyester and fibreglass tube Ø 32 mm with humidity-proof seals on each end, 3 defecting hoods, hand protector, grip, tip, Universal head and maneuvering hook. Indoor and outdoor use.



Mod. BME

Maneuvering Poles

Raw Material Features

Insulating tube: made of polyester and fiberglass. Blocking handles: polyamide PA66-GF30. Deflecting hoods: EPDM rubber. Screw: stainless steel.

Certified

Manufactured following the established by Standard **UNE-EN 50508** - Points **4.2**, **4.3**, **4.4** (in dry conditions) and **4.5**. Multi-purpose insulating sticks for electrical operations on high voltage installations.

Electrical Features

Ref.	Length	Working voltage
BME-45	1.60 m	45 kV
BME-66	2.10 m	66 kV
BME-132	3.10 m	132 kV



Datos sujetos a cambios 2017, Mayo 2 © 2017 Sofamel SLU Todos los derechos reservados.

Versión: R2-7.2 COM01

Las especificaciones están sujetas a cambios sin previo aviso.



Thomas Alva Edison, 16-17 - Pol. Industrial Plans d'Arau - 08787 La Pobla de Claramunt (Barcelona) - Spain Tel. +34 93 808 79 80 - Info@sofamel.es www.sofamel.com